

# Shanghai Unicorn Cable

Factory-direct UL & CSA certified wire and cable manufacturer

## Silicone Rubber Parallel Constant Wattage Heating Cable 15W/m

Part Number: SW-HEAT-SRCW-15-100 | Category: Heating Cable

Silicone rubber parallel constant wattage heating cable mainly used for antifreeze and heat preservation of pipelines. Maximum maintenance temperature 150°C, nickel-chromium alloy heating coil, 15W/m output, max circuit length 100m.

CONDUCTOR SIZE	VOLTAGE RATING	CURRENT RATING	TEMP. RATING
<b>2×0.75mm<sup>2</sup></b>	<b>220V</b>	<b>6.8A</b>	<b>-60°C to +200°C</b>

### Physical & Electrical Specifications

Conductor	2×0.75mm <sup>2</sup> Copper Bus Wires
Heating Element	Nickel-Chromium Alloy Heating Coil
Insulation	Silicone Rubber
Outer Jacket	Silicone Rubber
Gauge	2×0.75mm <sup>2</sup>
Voltage Rating	220V
Temperature Rating	-60°C to +200°C
Maintenance Temp	150°C (max)
Ampacity	6.8A
Power Output	15W/m
Max Usage Length	100m
Heating Node Distance	0.5m
Color	Transparent White
Packaging	100 m Drums
Circuit Type	Parallel Constant Wattage

### Certifications & Standards

Certifications: CE Marked, RoHS Compliant

Standards: IEC 60800, GB/T 19835

### Typical Applications

Pipeline antifreeze protection • Heat preservation of pipelines • Industrial process temperature maintenance • Roof and gutter de-icing • Freeze protection for water pipes

### Ordering Information

Minimum Order: 100 m | Packaging: 100 m Drums | Lead Time: 7-10 business days

+86-186 0163 8071