

Shanghai Unicorn Cable

Factory-direct UL & CSA certified wire and cable manufacturer

Multiple Cores Cable KFF/KFFRP-3 Shielded

Part Number: SW-KFFRP3-18-4C-500 | Category: Industrial Cable

Shielded multi-conductor fluorine plastic cable with tinned copper braid for EMI protection in high-temperature environments.

CONDUCTOR SIZE	VOLTAGE RATING	CURRENT RATING	TEMP. RATING
18 AWG	300V	10A per conductor	200°C

Physical & Electrical Specifications

Conductor	Tinned Copper Stranded
Insulation	FEP Fluorine Plastic with Overall Tinned Copper Braid Shield
Gauge	18 AWG
Voltage Rating	300V
Temperature Rating	200°C
Ampacity	10A per conductor
Color	Red/Blue/White/Black
Packaging	500 ft, 1000 ft Reels
Conductors	4
Shielding	Tinned Copper Braid 85%

Certifications & Standards

Certifications: UL Listed, CE Certified, RoHS Compliant
Standards: KFF/KFFRP-3, UL 1332

Typical Applications

Industrial control systems • Motor control • Servo drives • High-temp instrumentation

Ordering Information

Minimum Order: 500 ft | Packaging: 500 ft, 1000 ft Reels | Lead Time: 5-7 business days

0163 8071